EXECUTIVE ORDER A-006-1287 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP				VEHICLE TYPE C=passenger car; LDT≃light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; GVW=gross VW)	STAND (LEV=low e transitiona	LUST EMISSION LARD CATEGORY Imission vehicle; TLEV I LEV; ULEV=ultra LEV EV=super ULEV)		FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
2000	6	6GMXV03.5050				PC	11	LEV II" LEV	120K / 150K	Flexible-Fueled: Ethanol (E85) and Gasoline (Tier 2 Unleaded)					
No.		APORATIVE			lo.	SPECIAL FEATURES & EMISSION CONTROL SYSTEM		* = not applicable	OC/TWC=oxidizing/3-way c WU= warm-up cat. O2S/HO	at. ADSTWC=adsorbing TWC 2S=oxygen sensor/heated O2S					
1	6GI	GMXR0133880			1	TWC, HO2S(2), SFI	, EGR, OBD	AFS/HAFS-air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
2		* 3			2	*									
3		*			3										
4		<del></del> []			4	*									
EVAI No.	F	ECS No.	ENGIN SIZE (					ECT TO SFTP EUNDERLINED	ABBREVIATIONS:						
1		1	3.5			Chevrolet: Impala, Monte Carlo									
*		* *													
*	* * *				<u> </u>										
	•		* *												

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/ml]			G @ RA	AF=1.0 (*) AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of introgen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram										
CERT	T STD		NMOG NMHC		NMHC STD	mg=millig	mg=milligram ml=mile K=1000 miles F=degrees Fahrenhelt SFTP=supplemental federal test procedure										
0.048	3 0.	046	CERT		CERT [g/mi]	[g/mi]	CERT	[g/mi] STD	CER	Ox [g/mi] T ST		ERT M	STD	PM [g/	STD	CERT	STD
	- N. S.		0.052		<del></del>	0.075	0.7	3.4	0.02	0.0	5	1	15	*	*	0.004	0.07
		@ 50K		)54)		(0.075)	(1.0)	(3.4)	(0.01			(*)	(15) 18		$\longrightarrow$	(0.01) 0.01	(0.07)
		@ UL (0.052)			•	(0.090)	(1.0)	(4.2)	0.02	1	-	d	(18)	*	*	(0.01)	(0.09)
-	@ 50°F	8.4K	<u> </u>	•	*	•	*	*	•	*		*	*	•	*	*	*
	CO [g/mi] i SF @ 20°F &			2 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)				[g/mi] posite)					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50				= @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CER	STD	CERT	STD	CERT	STD
CERT	(1.9)			SF	TP @ 4K	*	*	*	*	(0.06)	(0.14)	(1.4)	(8.0)	(0.04)	(0.20)	(0.3)	(2.7)
STD	(10.0)			SF	TP @ UL	•	*	*	•	•	*	*	•	*	•	*	•
G	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				E۱	EVAPORATIVE FAMILY 4			
@ UL	3-D	2-	D	RL	ORVR	3-D	2-D	RL	ORVR	3 <b>-</b> D	2-D	RL	ORVE		2-D	RL	ORVR
CERT	0.35	0.4	10	0.00	0.01	*	*	*	*	*	*	*	*	*	*	*	*
STD	0.50	0.6	35	0.05	0.20	*	*	*	•	*	*	*	*	*	*	•	*

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of April 2005.

Allen Lyons, Chief

Mobile Source Operations Division